


T8



T8 TUBE SERIES

2FT		<ul style="list-style-type: none"> * LED: CREE 3528 SMD(0.06W*136PCS) * Length: 0.6m Beam Angel: 120° * Power Consumption: 9W, replacing 18W fluorescent lamp
3FT		<ul style="list-style-type: none"> * LED: CREE 3528 SMD(0.06W*200PCS) * Length: 0.9m Beam Angel: 120° * Power Consumption: 13W, replacing 30W fluorescent lamp
4FT		<ul style="list-style-type: none"> * LED: CREE 3528 SMD(0.06W*288PCS) * Length: 1.2m Beam Angel: 120° * Power Consumption: 18W, replacing 36W fluorescent lamp
5FT		<ul style="list-style-type: none"> * LED: CREE 3528 SMD(0.06W*340PCS) * Length: 1.5m Beam Angel: 120° * Power Consumption: 22W, replacing 58W fluorescent lamp

Technical Specification

	T8 2ft	T8 3ft	T8 4ft	T8 5ft
Length	0.6m	0.9m	1.2m	1.5m
Lampshade & Housing	PC, Aluminum Alloy	PC, Aluminum Alloy	PC, Aluminum Alloy	PC, Aluminum Alloy
Power Consumption(W)	9	13	18	22
Input Voltage	AC 100V~140V or AC190V~240V	AC 100V~140V or AC190V~240V	AC 100V~140V or AC190V~240V	AC 100V~140V or AC190V~240V
LED Quantity	136	200	272	340
LED Type	SDM(3528)	SDM(3528)	SDM(3528)	SDM(3528)
Lumious Flux(lm)	816+/-10%	1200+/-10%	1632+/-10%	2040+/-10%
CCT(k)				

	3000+/-250 4000 +/-250 6000+/-250	3000+/-250 4000 +/-250 6000+/-250	3000+/-250 4000 +/-250 6000+/-250	3000+/-250 4000 +/-250 6000+/-250
CRI	83	83	83	83
Socket	G13	G13	G13	G13
Package(mm)	320*260*665 1/20	320*260*965 1/20	320*260*1265 1/20	320*260*1565 1/20
Life Time(h)	50,000	50,000	50,000	50,000